

Specifications

Noahlink))) Wireless

Intended Use:

Noahlink Wireless is intended to enable a hearing instrument fitter to wirelessly adjust the settings of wireless hearing instruments. The primary function of the Noahlink Wireless programming interface is to transfer information signals between a PC installed with fitting software and wireless hearing instruments.

List of Countries:

Noahlink Wireless is a Class II communications device, and conforms to the essential requirements and other relevant provisions in over 20 regions and countries:

The declaration of conformity for these countries can be found in the *Noahlink Wireless Knowledgebase* at www.himsa.com.

Technical Specifications:

Operating range:	10 feet (3 meters)
Wireless (2.4 GHz):	BT LE: 2402-2480 MHz Proximity: 2404-2478 MHz
Modulations:	GFSK
Number of channels:	BT LE: 40 Proximity: 38 channels available but protocol chooses 16 out of 38
Data rate:	BT LE: 1/ Mbit/s Proximity: 2 Mbits/s
Output power:	BT LE: 4.264 dBm eirp Proximity: 16.457 dBm eirp
Antenna:	Internal antennas, Gain: 3dBi
Operating temperature:	0°C to 55°C (32°F - 131°F)
Storage temperature:	-20°C to 60°C (-4°F - 140°F)
Power supply:	Powered by the USB port of a PC
Operating Voltage:	5 VDC

Temperature test, transport and storage information

The product is subjected to various tests in temperature and damp heating cycling between -25 C and +70 C according to internal and industry standards.

Warranty:

The Noahlink Wireless programming interface is covered by a limited warranty issued by the manufacturer for a period of 12 months from the date of original purchase. Please notice that extended warranties may apply in your country. Please contact your local hearing instrument manufacture. Be aware of information marked with the warning symbol.

For More Information:

Please refer to the Noahlink Wireless User Manual, included with each Noahlink Wireless unit. The user manual can also be found in the *Noahlink Wireless Knowledgebase* at www.himsa.com.

